





THE

# TAILORS' GUIDE:

#5599

CONTAINING

SYSTEMS OF DRAUGHTING

## FROCK AND SACK COATS, PANTS,

VESTS AND SHIRTS.

WITH VALUABLE IMPROVEMENTS, WARRANTED SUPERIOR TO ANYTHING EVER OFFERED TO THE TRADE.



Ļ. E. COLI

7418

Copy Right Secured

MILWAUKEE:

starr  $\propto$  son, book and job printers, 412 and 414 east water street.

T 5 68

10-2512

## L. E. COLE'S

**IMPROVED** 

## SYSTEM OF DRAUGHTING COATS,

BY ACTUAL MEASUREMENT.

This system was first published by the proprietor in New York in 1835, and now republished with valuable improvements, such as have suggested themselves to him during a practical experience in using the same during the past thirty years, all of which is warranted to fit all shapes and sizes of men, without any variations in draughting, it being simply a transfer of inches taken on the man and applied on the cloth in draughting, precisely as taken thereby, producing a perfect fitting garment for all shapes and sizes of men, making it in all respects a perfect self varying rule or system of draughting coats; therefore I now offer this to the trade; and all I claim for it is: that you will give it your most critical and careful scrutiny as to its merits and practical utility; and believing that this system is what has long been wanted, by the trade, and that if once adopted will never be abandoned, I most cheerfully submit the same to your inspection and use.

L. E. COLE.

MILWAUKEE, May, 1868.

### ON MEASURING.

Plate 1 .- Figs. 1 and 2.

It is of the greatest importance in cutting, to measure with the utmost care and exactness; for if this be done in a loose and careless manner, exactness in delineating will avail but little. The first process towards taking a measure in this system is as follows: Let your customer stand in his natural position, with his hands on his hips, and his coat buttoned; then proceed: First make a mark at O, or where you wish the collar seam; also mark out  $2\frac{1}{2}$ inches on collar-seam, as at K, Fig. 1; next, mark at L, on Fig. 2, where you wish the center of back cye; next, place your tape or square at L and M, and mark on top edge of same on back seam as at B; next, place your square in front of arm—the short arm in front and pointing upward-crowd the same up in front of arm -also the long arm up, as snug under the arm as the customer wishes the coat; while in this position, mark in front of square as at H, opposite the top edge of square; also mark at I, on Fig. 2; then place the square across the back, ranging with I, and mark at C on back seam; next mark at D, the natural waist, and at E full length; next mark out on hip, near where side piece is cut off, say 7 inches from D to I; next, mark at P 2 inches from front of coat at waist; next, extend the line from H to G and to front of breast; at 8 next mark out his line from H to G 4 inches; next mark at P, Fig. 1, and at 8 on breast, and at N or the throat. You are now ready to take your measure.

Commence at O A, Fig. 2, and measure down to B  $5\frac{1}{2}$ , and to C  $8\frac{1}{2}$ , and to D 17, and E 19, and full length skirt 36 inches; next, place your tape measure at H and measure across under arm by I, Fig. 2, to C on back seam 12 inches, and up to O 16 inches; next, from H up to K, on Fig. 1, or to where  $2\frac{1}{2}$  inches is marked; on Fig. 2,  $9\frac{1}{2}$  inches, and to O, on Fig. 2, 12 inches; and from same point, over shoulder, to B, on Fig. 2,  $14\frac{3}{4}$ , and to C on 2,  $16\frac{3}{4}$  inches, from same point to J 9 inches, and from same point to P,  $11\frac{1}{2}$  inches; next commence at G and measure up to N 7 inches, and to K  $9\frac{1}{2}$ , and over shoulder to B  $15\frac{1}{2}$ , and to L, on Fig. 2, 11, and to I 15 inches, and next

down to P 10½ inches; next, from D to J 7 inches; next raise the arm up on a level with B on back, and bend the elbow at right angles with back, and measure from B to M 7½ inches, and to elbow 20, and to hand 32; next measure across breast from arm to arm, or 8 to 8, 16 inches, and round neck 16 inches, over vest collar; next, round breast 36 inches, and waist 32 inches. Breast and waist measure over vest.

To draught back, draw line on edge of cloth; then commence at O, and draw line down to E, about two inches in from edge of cloth, or first line at. E, and square top of back from O to dot on top of back, then measure down from O to B  $5\frac{1}{2}$ , and to C  $8\frac{1}{2}$ , and to D 17, and E 19 inches, and full length of back 36 inches; then measure from O to dot  $2\frac{1}{2}$ , and from B to back eye on line B  $7\frac{1}{2}$  inches, and from E width back at waist 2 inches, or as you wish; next, form the shoulder, top of back, and side seam as represented.

To draught forepart, lay the back on the cloth where it will come out best, then extend line C across by H and G to front of breast, or as far as necessary; then measure from C to H 12 inches, and to G 16 or 4 inches from H, and to front of breast 20 inches, or 8 inches from H; next, measure from H under arm and up to O, 16 inches, as taken on the man, measure from H to cye, the width of square as applied in measuring, and square up in front of eye as represented; then form back part of de and botton, and up to line 4; next measure from H up to K 9½ inches, and up to A 12 inches; mark in the same range  $14\frac{3}{4}$  and  $16\frac{3}{4}$  as taken over to B and to C, then sweep from H by K 9½, and by 12, 143 and 163; next mark from H to J 9 inches, and to P 11½ inches; next, commence at G and measure up to N 7 inches, and to K  $9\frac{1}{2}$ , and over shoulder to B  $15\frac{1}{2}$  inches, and to center of back eye or L, 11½, and to 1 15 inches, and from same point to J 11 inches, and to P 10½ inches; next, sweep from H by J 9 inches, and from G by J 11 inches; next, from where sweep crosses at I, measure back to D 7 inches; next, carry the back in at waist letting it turn on the dot at shoulder blade, until the outside of back at D rests on sweep inches from J; this gives the coat the exact spring at waist; and while the back is in this position, mark side seam from shoulder blade to bottom of waist, as per dotted lines, hollowing it a little; then draw line from eye down to waist at I and form bottom of side piece to I; next,


sweep from H to P  $11\frac{1}{2}$  inches, and from G by P  $10\frac{1}{2}$  inches, and measure from J to P 9 inches, and form waist seam as represented; next, sweep from G by K  $9\frac{1}{2}$ , and by B  $15\frac{1}{2}$  inches, then place the back, the dot, or  $2\frac{1}{2}$  inches from A, on the point where the two sweeps, cross at K from H and G, and the point at B on back seam; on the point where the two sweeps, cross from H to B  $14\frac{3}{4}$ , and G to B  $15\frac{1}{2}$ , and while the back is in this position form the shoulder seam and the remainder of cye, and gorge from A and K to N 16 inches, and allow one inch for making up; then form breast from N to P, the length as taken on the man; also apply waist measure from D to J and to P, and allow 2 inches for making up for fish.


#### TO DRAUGHT FROCK COAT SKIRT.

Obtain the pitch of skirt in front by laying the forepart on in a joining position at waist, and drawing a line running in range of front of breast to about 3 inches in from the bottom of skirt in front; also place the side piece in a joining position at waist, and mark the fold in range of side seam to bottom of skirt, then round the fold as per diagram.

To draught sleeve, draw a line on the edge of cloth, or where you wish to take out the sleeve, and square cross top from R to A is one inch, and to S 4 inches or width of cye, then square from S to T, measure from S to T 8 and from D to 8—8 inches or half the size of cye, draw line from 11 by 8, 8 inches from and parallel with front line, or half the size, then form from S the top of sleeve head to 11, then take off width of back and measure to elbow 19 and to hand 32, length of sleeve; add on 2 inches at elbow from 8 to 10, and form sleeve as represented, any width at hand you choose; form under side as represented.









				_										_	
of Inches for Draughting Coats by Inch Tape Measure. Plate 1—C D E F and G.	Round Waist.	85	30	31	31	35	33	33,2	34	35	36	361,2	36,1	36	36,2
	To Hand.	98	30	31	31,2	33	32,5	35	33	3312	34	34	35	35	35
	To Elbow.	1 82	ñ/81	5,61	06	06	20		20,02	- 15	211°	2112	65	8	83
	Width Back.	159	6,2	-	714	7,5	734	73/ 20	- ∞	œ	8,4,8	834	6	914	91,5
	Round Neck.	15	151,1	15/2	1534	16	1615	63,7	17	11	7	714	171/2	173,	81
	Cross Breast.	12	15,4	15,51	153,1	16 1	614 1	1634 1634	17	17 1	17,4 17	171,6 171,4	173,1	18	18
	From G to P.	91,1	934 1	10 1	10,14	10%1	15,4 11,4 103, 1614		111/4	11/2/11	11,12	1134 1		12,4	12,2
	From G to J.	2	10,4		1034 1		1,41	1214 1512 1115 11	24			74	21/2 12	12,34	
	L of L mon F	Ī	177	1436 1012	1434	Ξ	5,41	517	153,111	3 12	314 12	16,2 12	1112 1714 1314 1634 12,12		1334 1715 13
	From G to L.	11/4 14	1112 1414	11)2 14	34 14	15		17,10	12/21	12,2 16	$123_4 16^1$		1416	11 27	3,11
		Ī			14 1134	15/2 12	3, 12		14	21 27		13	14 13	17,5 13,	34 113
	From G to B.	14	914 1434	91,2 15	934 157		1, 153,	101,5 16	34 16	$10^3$ , $16^{\circ}$	1634	1114 17	11 11	34 17	1734
	from G to N.	6	614 9	6,2 9	634 9	10	101	714 10	712 1034	01 274	11 2/1	73, 11	Ξ	81, 113,	8,3 12
	Measures taken	9	6,4 6	6,2 6	634 6	7	7	71/2 7	11 512			7	00	8,2 81	
	L1 of G mon7	9		6,1		\S1	1 714	7.	7.	2 734	00	00	4 814	8	4 83,
	From H to P.	101/2	1034	11	1114	111,5	1134	ã 15	13	121	12j	15	1234	13	131
	From H to J.	00	18	5/8	834	6	9,4	91	91,2	916	6	91,5	93,	10	1914 1014 131
	To C.	91	16,4	$16\frac{1}{3}$	163	17	1714	1712	173,	18	$18^{14}$	$16^{1}_{4}$ $18^{1}_{2}$	1612 183	61	191
	. '8 oT	133	14	1414	141	143	15	1514	$15_{12}^{12}$	15,3	16	1614	161	14 1634	17
ghti	To A-top back.	111	1134	2	12,1	12,2	123,	13	13	13,4	$13_{12}$	133,	7	1412	141, 17
Table of Inches for Drau	т₀ к.	6	6,'6	910	934	10	1014	1012	10,3	103,	=	$13^3_4\ 17\%\ 111_4$	111	113,	22
	.0 of qU	15	$15^{1/4}$	151	$153\frac{1}{4}$	91	1614	161,3	$16^{3}_{4}$	17	171,	17,15	173	18	181
	Measures taken from H to C.	10,4	103	1118	1137	2	12,5	12,0	123,	13	8,4 131, 17	$13^{3}_{4}$	14	141	91, 141, 18,
	Width Back.	614	613	7	717	7.5	75%	73,	œ	တ	814	25.2	83,	6	91,4
	.tsisW latural	1613	163,	17,2	173,	18	18	181,	181	183	19	19	1914	1912	1934
	Level under Arm	71,4	7,2	တ	81,	218	85/8	83,	87,8	6	91,	91,4	91,2	93,	
	Cye.	41/2	43.	9.	P1.5	5,10	513	53,4	9	61,4	ã,9	ē 19	63,	7	7,4 10
	O Width Back at Top.	50.	. c	C	21,2	2,3	1€ 51	1 <u>0</u> 2	2,2	21.5	 	20.00	က	က	m
	1- 1-20 are in C	33	33	34	35	36	37	38	39	9	7	27	43	4.4	45
						-	-				==				



### L. E. COLE'S

## IMPROVED SELF VARYING SYSTEM

OF

## DRAUGHTING PANTS,

ON NEW PRINCIPLES. Copy Right Secred Jan. 18. 1859.

This system is entirely new with the proprietor, and first published in 1858 and now republished with valuable improvements, and warranted to fit all shapes, either corpulent or regular form, without any variations in draughting; all pants being draughted by this system precisely the same, and nothing would induce him to republish this system at this time but a firm belief that it is not only the best, but the only system ever published founded upon true scientific principles of actual measurement, every part being draughted by its own measure thereby giving to each part the exact quantity of cloth required and in the right place, and no more. The important features of this system differing from all others are the establishment of a base or working line running from the waist to the instep through the centre of the leg, and by working each way from this line at waist, thigh, knee and bottom, giving to each part the number of inches called for and no more. Pants draughted by this system never twist, but always hang perfectly square and can be cut any shape either half and half on each side of base line or top side narrow at any part, as what comes off from top side is added to under side, always allowing one-half the size of leg at any part on each side of base line, as that is the center of both top and under sides, center of instep and center of heel, center of knee, thigh and waist. I think a glance at the principles of this system and its working, is sufficient to convince any practical cutter of its superiority over any and all other systems now in use. Hundreds of testimonials of its superiority could be given from those now using it, but it is deemed unnecessary as the principle fully shows for itself, and feeling the fullest confidence that this system, if once adopted, will never be abandoned, I cheerfully submit it to your inspection and use.

L. E. COLE.

MILWAUKEE, May, 1868.

### TO MEASURE FOR PANTS.

Plate 2.

Commence at top of hip bone and measure down to knee, 22 inches, and to bottom 42; next inside leg measure to sole of boot next to boot heel 32 inches, next round waist, hips, seat, thigh, knee, bottom; 28-34-36-21-17-17.

To draught upper side or diagram A by this system, first draw line on edge of cloth from O to C at bottom, next measure down from O to B 22 and to C 42, next up to A 32, next draw line from A to D 21 inches in from C, next measure in from D to K 17, scale A bottom measure next sweep from K by P to N at knee and from A to H at thigh, and from O to I at waist, next measure in from A to E 21, scale A, thigh measure; next draw base line or working line from K by E to J at waist and from this line you work each way by placing the center of draughting scale on this line, the protractor pointing down and mark out each way from waist, thigh, knee and bottom according to the measures taken, as each part is draughted by its own measure, no one measure having anything to do with the other; place the scale on base line at waist and mark each way 14, scale A waist measure, next mark out from E to A 21, scale A thigh measure, and to F 21, scale B, and to G 21, scale A thigh measure, and add the dress to H, then place center of scale at M and mark each way to P and N, scale A knee measure, next from K to L 17, scale B bottom measure, then draw line from F to I and from G to N and L at bottom, then form I to G and from I to H for dress, and from A to R and from H to N and bottom as represented.


To draught under side or diagram B, lay the upper side on the cloth where it will come out best; then extend the base line from I to U, next extend the sweeps from G to S and from J to T at waist, from J to T is one-fourth the size of waist, and V taken out, from G to S is 21, scale C thigh measure, add to under side at N till they will make up the required size, 17 inches, also add from 17 upper side at bottom to 17 under side till they make up 17 inches, the required size as per measure; from J to U is 14, scale A waist measure, on sweep from F by R; see diagram A; draw line from U to T, and take out V, and form top as represented; draw line from U to C at fork, next apply hip measure 34, and from 3 to 4, seat measure, 36 inches, then form from U to C and S, and from T to knee and to bottom as represented, dropping the point at SS, about one inch, and stretching the same up as marked on diagram B; also stretching in the curve at G, C on under side has a very beautiful effect in the fit of pants.

Diagram C is draughted the same as diagram B in all respects, giving to each part the required number of inches called for as taken on the man—it shows the difference between the regular form and the corpulent one. This being the form of the corpulent man, and the distance each way from J to K and J to I being 21 each way, instead of 14 on the regular form at waist, and from 3 to 4, seat measure, 44 instead of 36 on diagram B.


I think this illustration of the different forms, and the different shapes produced, will convince any practical cutter of the true self varying principles of this system over any other system.


Diagrams D and E are on the same principle of draughting, only showing the manner of draughting side band goods, as you cannot hollow the top side at knee, it requires all the hollowing on the underside at the knee, as represented on diagram D.


Diagram E shows the manner of taking the measure as applied on diagram A and B.











## L. E. COLE'S

IMPROVED

## SYSTEM OF DRAUGHTING COATS,

BY ACTUAL MEASUREMENT.

# TO DRAUGHT SACK COAT AND SHORT BUSINESS FROCK.

Plate 3.

This plate contains the draught of Sack Coat in full, also Short Business Frock.


In measuring for Sack Coat you proceed the same as for Frock Coats, on plate 1, figs. 1 and 2, except you will not measure to or mark at J at hip, or at P at front of waist. After marking all the necessary points, you will take your measures as follows: from O to B 5, and to C 8 and to D natural waist 16, and to bottom 30 inches; next place your tape at H, and measure across under arm to C 12 inches, and up to O A 16 inches, next from H to K  $9\frac{1}{2}$ , and to O 12 inches, and over to B  $14\frac{3}{4}$ , and to C  $16\frac{3}{4}$  inches, next commence at G and measure to N 7 and to K  $9\frac{1}{2}$  and to B  $15\frac{1}{2}$  inches from G to center of back cye, to center of back cye  $11\frac{1}{2}$  and to I 15 inches, next place the arm at right angles and measure from B to M  $7\frac{1}{2}$ , and to elbow 20 and to hand 32 inches, next across breast and around neck 16 and 16 inches, next around breast 36 inches.

To draft back, commence at O and measure down to B 5, and to C 8, and to waist 16, and full length 30 inches; width of back at top  $2\frac{1}{2}$  inches; square across at B and C and D and at bottom; next measure out on line B  $7\frac{1}{2}$ , and on line C 6 inches; draw line from 6 to bottom of back parallel with back seam, and from the back as you please.


To draft forepart, place the back on the cloth, and extend line across to front of breast, then measure from C to H 12 inches, and to G 16 or 4 from H and to front of breast, and allow 2 inches from 8 to front; measure back from H to eye 1 inch or width of square, as use in measuring, then square up in front of cye as per diagram; next place tape at H and measure up to K  $9\frac{1}{2}$ , and to O, top back, 12 inches; measure in same range  $14\frac{3}{4}$ and  $16\frac{3}{4}$  inches; then sweep from H by K  $9\frac{1}{2}$ , 12,  $14\frac{3}{4}$  and  $16\frac{3}{4}$ inches; next commence at G and measure up to N 7, and to K 91, and to B 153 inches; next from G to L 111, and to I 15 inches; next place the back on point  $2\frac{1}{2}$  inches, touching point where sweep from H and G crosses at K, and point B where sweep from H and G crosses at B on back, then form the shoulder seam, and form gorge from K to N; next from eye and breast add on about two inches at bottom of forepart at back, and draw line from line D to bottom, and shape side seam as per diagram.


To draught sleeve, from O to 1 is 1 inch, and to 4 is 4 inches, or width of cye; from 4 to 15 is 15 inches or size of cye; draw line 15 to bottom of sleeve parallel with front line; allow about 2 inches at 19; place the back at top of sleeve, and measure from outside of back to elbow at 19, and to 31 length of sleeve 31 inches, and form sleeve as represented.

Diagram A, B, C, D, are draughted the same in all respects as frock coat on Plate 1.









### TO DRAUGHT OVER COAT AND CAPE.

Plate 4.

To draught this over-coat and cape, you will proceed in all respects the same as in draughting sack under coat, on plate 3, except you will add to all the measure taken from O, E and F, as follows: from O to B 1 inch, and from E to B 1 inch, and from E to O at top of back, and to H, A, B, each 1 inch, as you will see the allowance is made already in the draught, and marked in figures on the lines, as from E to B  $13\frac{1}{2}$  instead of  $12\frac{1}{2}$  as taken on the man; also from E to H, A and B  $13\frac{1}{2}$ ,  $15\frac{2}{4}$ , and 18, instead of  $12\frac{1}{2}$ ,  $14\frac{2}{4}$ , and 17, as taken on the man; also allow 2 inches across breast in forming all parts. See diagrams A, B and C.

This diagram shows a very good way of cutting a first rate fitting cape by the gorge of coat with the back in a joining position.

### TO MEASURE FOR VEST.

With Delineator.

Take the length from socket bone at neck over shoulder and down to hip and in front, then round the breast, waist and neck, also the heighth of roll. This vest is draughted by a delineator made for the purpose, and warranted good. In draughting vest, proceed as follows: Draw line on edge of cloth, then draw 2d line 2 inches inside and parallel with the first and square the top, then take the delineator and place the edge of same on inside line and let the figures 36 rest on the top line; then mark along in the different spaces and along the bottom of delineator, and then mark at 36 in each space and on the front and bottom, then form the vest from point to point marking from one point to the other by the marks made at the figures 36, or any other size you wish to draught as the figures in the space all indicate the different breast measures and are all applied as above.

The back is draughted the same way by placing the delineator on line O fig. 36, at top resting on top line, then mark in all the spaces as in draughting forepart then forming from one point to the other.

This delineator cuts a beautiful fitting vest and cannot be beat.

#### TO DRAUGHT SHIRT.

Plate 4.


Diagrams A, B and C of shirt draught, shows a plan of draughting a shirt; and I guarantee it to be one of the best fitting shirts ever got up in this country. It is all right.


The measures for shirt are taken as follows: first measure from O length of shirt, next length of sleeve from Socket bone at O, letting the arm hang down, measure from O over the shoulder down to hand, say 32, and full length of wrist band 34; next round neck 16, and breast 38 for this draught. This draught is 38 breast,


To draught the back, commence at O, from O down to 1 is 1 inch; to 2 is  $3\frac{1}{4}$ , to 3,  $8\frac{1}{4}$ ; to 4,  $11\frac{1}{2}$ ; to 5,  $20\frac{1}{2}$ ; to 6, 31; and to A, 35 inches. Square out from line O at 2, 3, 4, 5, 6 and A; next mark out on top from O to T  $2\frac{1}{2}$  inches; next out on line 2,  $9\frac{3}{4}$ ; on 3,  $9\frac{1}{2}$ ; on 4, 12; on 5, 10; on 6,  $12\frac{1}{2}$ ; form bottom of back from A to  $12\frac{1}{2}$ ; where shirt is left open at bottom, draw line from T to  $9\frac{3}{4}$  to  $9\frac{1}{2}$  and to C, and from 12 by 10 to  $12\frac{1}{2}$  as represented.


To draught front of shirt, commence at O; measure down 2,  $3\frac{1}{2}$ ,  $7\frac{1}{2}$ ,  $10\frac{1}{2}$ ,  $10\frac{1}{2}$ , 30 and 34 inches; then square out from 1, 2, 3, 4, 5 and B; next measure in from O  $3\frac{1}{2}$ ; at 2,  $2\frac{1}{2}$ ; and on line 2,  $9\frac{1}{2}$ ; line 3, 12; line 4,  $12\frac{1}{2}$ ; line 5,  $12\frac{1}{2}$ ; and form line B as you see to  $12\frac{1}{2}$ ; draw line from A to D, and form from D by  $9\frac{1}{2}$  to C, and from C by  $12\frac{1}{2}$  to  $12\frac{1}{2}$  at bottom as represented; next cut a piece the shape of a yoke, and place on as you see, covering shoulder seam, to be be stitched on same as yoke.

Diagram C or sleeve: commence at O, measure down on O line  $2\frac{1}{2}$ ,  $11\frac{1}{2}$  and 22; square out O line, and at 1, 2, and at hand 6 inches; then form sleeve as per diagram. Make cuff any width or size you wish.









	From 3 do.	43,4	5	514	215	534	9	$6^{1/4}$	61/2	634	7	714	712	734	00
	From S do.	734	00	814	8/2/	83,	6.	91,4	37,8 1012 912 612	1214 2234 4 1034 934	0	312 123 2314 415 1114 1014 714	33413 2312 434 1112 1012 712	4 131/233/ 5 113/103/ 73/	
	From 1 Cross.	83/		916	9,9	93/			115	)3/4	-	14	1 2	34.1	
	S of 0 mont azon0	27.8	e0	31/8	3,4	33/8	31,9 10	334 1014	378	=	41/2 11 10	1 3 1	3/4	Ξ.	51/4 12 11
ပ	To 3 do.	t		14		67.		7/4	2212	27.	-	14 4	755	70	
and	To 2 do.	101,4 203,4	11/4 1012121	112 103 2114	13, 11 211,2	1114 2134	$2^{1}_{4}$ $11^{1}_{2}$ $22$	2,2 113, 2214	65	14 22	81/4 121/2 23	3/23	- 23	123	4141319 24
м В	From O down fo 1.	12	4 10	5 TO	11	Ξ	11	=	23/ 12	13	4 12	2 12	4/13	13	4,113
~!	From O down					C?				භ -	31	31	. 33	44	4
SHIRT SLEEVE.															
4	From 5 do.	12%	11/2	1134	27	1214	151	1234	65	13/4	131/2	33,	4	413	100
te	From 4 do.	1014	1012	1034	=	114	- ° °	13/	C)	214	1212 1312	234	es .	314	31211
Pla	From 3 do.	03	=	17%		13/4	- 2	21/4/1	2,2,1	237		314 1	31,21	334 1	-
g	From 2 Cross.	87,8 103, 101,4 111,4	6,111 6,101 11, 6	91811	91,4111,2,111,12	93,1	915 1	958 1214 1134 1234	934.121,2,12 13	97, 123, 121, 131,	1 0	018 1	014 11.	038 1.	_
ည်	From 1 to D.	101	1013	03/4		11/4	7.1	15,8		%.	- 2	11/8 11	214 1	38/1	12/2
Measure, on Plate 4—A B	From O Cross to	27/8		318 1034 918 1114 1034 1134	314 11	338 1114 938, 1134 1114 1214	$3^{1}_{2}$ $11^{1}_{2}$ $9^{1}_{2}$ $12$ $11^{1}_{2}$ $12^{1}_{2}$	35,8 115,8	33, 11	=	41/8 12 10 13	1/4 19	438, 1214, 1014, 1312, 13 14	412 1238 1038 1334 1314 1413	43/4 12/2 11 14 13/2 14/2
Mea	To B do.	323		14		6/4			7.01	27	_	4 4	61		
e e		3, 32	333	14 33	$29^{1}_{2}$ $33^{1}_{2}$	34 33	34	14 34	1,34	34	35	4 35	12 35	3, 35	98
Tar	To 5 do.	912 1814 283	93, 181, 29	3, 29		6: 4	30	18 30	37 30	8 30	31	8 31	4 31	5 31	33
, q	.ob + oT	81	181	<u>x</u>	4 19	8 19	9 19	8 195	4 193	8 197	30	8 201	4 201	8 201	5 203
2	To 3 do.	-	50	-	=	3	-0	5/	23	13	Ξ	-1		60/	11
片				- 8	1	78	- 2	1 8	1,1	Ξ.	= ,	=======================================	=	=======================================	-
oy Ir	.ob S oT	67%	4	8 718 10 1834 2914 3314	1 214:1014 19	3 738 1038 1914 :934 3334	715 1012 1913 30	758 1058 1958 3014 3414	1 734 1034 1934 3012 3412 334 1134	778 1078 1978 3034 3434 4 1178	8	81/8 111	814 111, 2014 31, 2 3512	838 1138 2016 3134 3534	81,2 111,5 203, 32
ts by Ir			3 7	3,18	3,4	33/8	3,5	3,58	33/4	37%		41/8 81/8 111/8 201/8 311,4 351/4 41/4 121/8 101/8 131/4 123/4 133/4	41/4 81/4 11	43, 83, 11	41, 81, 1
irts by Ir	.ob S oT	67%	3 7	Z 318	3,4		3.5°	3.58		37%		41/8 81/8 11	41/4 81/4 11	438 838 11	41, 81, 1
Shirts by Ir	Trom O down t of	278 678	.⊤. 	Z 318	⊃.E.	% % E.I	3.5°	35,8	33	0 378	8		41/4	43,8	41,
g Shirts by Ir	From 6 down from 10 down 10 story 10 story	278 678	.⊤. 	Z 318	⊃.E.	% % E.I	121 <sub>2</sub> H 31 <sub>2</sub>	35,8	33	0 378	8		41/4	43,8	41,
ting Shirts by Ir	From 5 do. From 6 do. From 0 down to 1.	834 1134 278 678	9 1112日 3 7	914 1134 7 318	912 0 314	% % E.I	10 12 <sup>1</sup> 2 F 3 <sup>1</sup> 2	35,8	33	0 378	8		41/4	43,8	41,
ughting Shirts by Ir	From 4 do. From 5 do. From 6 down From 0 down 1 of 1.	1034 834 1114 278 678	11 9 1112 F 3 7	914 1134 7 318	912 0 314	% % E.I	10 12 <sup>1</sup> 2 F 3 <sup>1</sup> 2	35,8	33	0 378	8		41/4	43,8	41,
Draughting Shirts by Ir	From 3 do. From 5 do. From 6 do. From 0 down to 1.	878 1034 834 1134 278 678	9 11 9 1112 F 3 7	918 1134 914 1134 2 318	9/4 1112 912 12 0 314	938 1134 934 1234 日 338	91g 12 10 121g F 37g	958 1214 1014 1234 1 358	934 1212 1012 13 1 334	978 1234 1034 1314 [] 378	8		41/4	43,8	41,
or Draughting Shirts by Ir	From 2 do. From 3 do. From 5 do. From 6 do. From 6 do. From 0 down to 1.	9 878 1034 834 1134 278 678	914 9 11 9 1112 F 3 7	938 918 1114 914 1134 7 318	912 914 1112 912 12 0 314	958 938 1134 934 1214 1 338	934 91e 12 10 121e F 37e	978 958 1214 1014 1234 H 358	10 934 1212 1012 13 1 334	1018 978 1234 1034 1314 10 378	8		41/4	43,8	41,
for Draughting Shirts by Inch Tape	From 0 Gross to T.  From 2 do.  From 3 do.  From 4 do.  From 5 do.  From 6 do.  From 0 down  to 1.	178 9 878 1034 834 1134 278 678	2 914 9 11 9 1112 F 3 7	218 938 918 1114 914 11134 7 318	2/4 9/2 9/4 1112 9/2 12 0 3/4	238 958 938 1134 934 1234 日 338	212 934 912 10 1212 H 315	234 978 958 1214 1014 1234 H 358	27,8 10 93,4 121,2 101,2 13 1 33,4	3 1018 978 1234 1034 1314 [] 378	318 1014 10 13 11 131 <sub>2</sub> 4 8	314 1038 1018 1314 1114 1334	312 1012 1014 1315 1112 14 414	358 1058 1038 1334 1134 1414 438	378 103 1015 14 12 1415 415
hes for Draughting Shirts by Ir	From 0 Cross to 1. Trom 0 Cross to 2. Trom 2 do. From 3 do. From 5 do. From 5 do. From 6 do. From 6 do. From 6 do. 7 of 2 do.	178 9 878 1034 834 1134 278 678	34 2 914 9 11 9 1112 F 3 7	218 938 918 1114 914 11134 7 318	2/4 9/2 9/4 1112 9/2 12 0 3/4	238 958 938 1134 934 1234 日 338	934 91e 12 10 121e F 37e	234 978 958 1214 1014 1234 H 358	27,8 10 93,4 121,2 101,2 13 1 33,4	3 1018 978 1234 1034 1314 [] 378	8	314 1038 1018 1314 1114 1334	312 1012 1014 1315 1112 14 414	358 1058 1038 1334 1134 1414 438	41,
Inches for Draughting Shirts by Ir	From 0 Gross to T.  From 2 do.  From 3 do.  From 4 do.  From 5 do.  From 6 do.  From 0 down  to 1.	178 9 878 1034 834 1134 278 678	30 34 2 914 9 11 9 111 <sub>2</sub> F 3 7	218 938 918 1114 914 11134 7 318	2/4 9/2 9/4 1112 9/2 12 0 3/4	238 958 938 1134 934 1234 日 338	35 212 934 919 12 10 1212 H 315	234 978 958 1214 1014 1234 H 358	27,8 10 93,4 121,2 101,2 13 1 33,4	3 1018 978 1234 1034 1314 [] 378	318 1014 10 13 11 131 <sub>2</sub> 4 8	314 1038 1018 1314 1114 1334	312 1012 1014 1315 1112 14 414	358 1058 1038 1334 1134 1414 438	37 378 103 1019 14 12 1419 419
of Inches for Draughting Shirts by Ir	From 0 Cross to 1. Trom 0 Cross to 2. Trom 2 do. From 3 do. From 5 do. From 5 do. From 6 do. From 6 do. From 6 do. 7 of 2 do.	178 9 878 1034 834 1134 278 678	30 34 2 914 9 11 9 111 <sub>2</sub> F 3 7	218 938 918 1114 914 11134 7 318	2/4 9/2 9/4 1112 9/2 12 0 3/4	238 958 938 1134 934 1234 日 338	35 212 934 919 12 10 1212 H 315	234 978 958 1214 1014 1234 H 358	27,8 10 93,4 121,2 101,2 13 1 33,4	3 1018 978 1234 1034 1314 [] 378	32 36 31 <sub>8</sub> 10 <sup>1</sup> / <sub>4</sub> 10 13 11 13 <sup>1</sup> <sub>2</sub> 4 8	314 1038 1018 1314 1114 1334	312 1012 1014 1315 1112 14 414	358 1058 1038 1334 1134 1414 438	37 378 103 1019 14 12 1419 419
ole of Inches for Draughting Shirts by Ir	To 6 do.  A cT From 0 Cross to T From 2 do. From 3 do. From 5 do. From 5 do. From 6 do. From 6 do. From 6 do.	178 9 878 1034 834 1134 278 678	30 34 2 914 9 11 9 111 <sub>2</sub> F 3 7	218 938 918 1114 914 1134 7 318	912 914 1112 912 12 0 314	238 958 938 1134 934 1234 日 338	35 212 934 919 12 10 1212 H 315	234 978 958 1214 1014 1234 H 358	27,8 10 93,4 121,2 101,2 13 1 33,4	3 1018 978 1234 1034 1314 [] 378	32 36 31 <sub>8</sub> 10 <sup>1</sup> / <sub>4</sub> 10 13 11 13 <sup>1</sup> <sub>2</sub> 4 8	314 1038 1018 1314 1114 1334	312 1012 1014 1315 1112 14 414	358 1058 1038 1334 1134 1414 438	37 378 103 1019 14 12 1419 419
Table of Inches for Draughting Shirts by Ir	10 & 6 of  10 & 6 of  10 A  From 0 Cross to  10 S do  From 5 do  From 5 do  From 6 do  From 6 do  From 6 do  From 6 do	712 1034 1978 2934 3334 178 9 878 1034 834 1114 278 678	734 11 20 30 34 2 914 9 11 9 112 片 3 7	938 918 1114 914 1134 7 318	8 111/2 2014 3012 3412 214 912 914 1112 912 12 0 314	818 1138 2038 3034 3134 238 958 938 1134 934 1214 1 338	814 1112 2013 31 35 212 934 912 12 10 1212 H 315	83,8 1158 2058 311,4 351,4 23,4 97,8 958 121,4 101,4 123,4 \(\frac{\pi}{4}\)	81,2 1134 2034 311,2 351,2 27,8 10 934 121,2 101,2 13 1 334	858 1178 2078 3134 3534 3 1018 978 1234 1034 1314 [] 378	83,112 21 32 36 318 1014 10 13 11 1312 4 8	87, 121, 211, 321, 361, 31, 1103, 101, 131, 111, 133,	41/4	918 1258 2112 3234 3634 358 1058 1038 1334 1134 1414 438	37 378 103 1019 14 12 1419 419
Table of Inches for Draughting Shirts by Ir	10 5 do.  10 5 do.  10 6 do.  10 6 do.  10 A o.  From 0 Cross to  From 3 do.  From 5 do.  From 5 do.  From 6 do.  From 6 do.  From 6 do.  From 6 do.	23/4 7/2 103/1976 293/3 333/4 17/8 9 87/8 103/4 83/4 111/4 27/8 67/8	278 734 11 20 30 31 2 914 9 11 9 1112 F 3 7	218 938 918 1114 914 1134 7 318	111/2 2014 3012 3412 214 912 914 1112 912 12 0 314	238 958 938 1134 934 1234 日 338	35 212 934 919 12 10 1212 H 315	83,8 1158 2058 311,4 351,4 23,4 97,8 958 121,4 101,4 123,4 \(\frac{\pi}{4}\)	312 812 1134 2034 3112 3512 278 10 934 1212 1012 13 1 334	33, 858 1178 2078 313, 353, 3 1018 978 123, 103, 133, 10 378	33, 83, 12 21 32 36 318 1014 10 13 11 1312 4 8	378 878 1218 2118 3214 3614 314 1038 1018 1314 1114 1334	4 9 12/4 2114 3212 3612 312 1013 1014 1312 1112 14 414	418 918 1258 2112 3234 3634 358 1058 1038 1334 1134 1414 438	37 378 103 1019 14 12 1419 419
Table of Inches for Draughting Shirts by Ir	10 \$ 40.  10 5 40.  10 5 40.  10 6 40.  10 8 40.  From 0 Cross to From 2 40.  From 5 40.  From 5 40.  From 5 40.  From 6 40.  From 6 40.  From 5 40.	712 1034 1978 2934 3334 178 9 878 1034 834 1114 278 678	734 11 20 30 34 2 914 9 11 9 112 片 3 7	218 938 918 1114 914 1134 7 318	8 111/2 2014 3012 3412 214 912 914 1112 912 12 0 314	818 1138 2038 3034 3134 238 958 938 1134 934 1214 1 338	814 1112 2013 31 35 212 934 912 12 10 1212 H 315	234 978 958 1214 1014 1234 H 358	81,2 1134 2034 311,2 351,2 27,8 10 934 121,2 101,2 13 1 334	858 1178 2078 3134 3534 3 1018 978 1234 1034 1314 [] 378	83,112 21 32 36 318 1014 10 13 11 1312 4 8	87, 121, 211, 321, 361, 31, 1103, 101, 131, 111, 133,	12/4 2114 3212 3612 312 1013 1014 1312 1112 14 414	918 1258 2112 3234 3634 358 1058 1038 1334 1134 1414 438	378 103 1015 14 12 1415 415
Table of Inches for Draughting Shirts by Ir	10 2 do. 0 4 do. 10 4 do. 10 5 do. 10 5 do. 10 6 do. 10 A OT 10 S do. 10 Cross lo 10 Cross	23/4 7/2 103/1976 293/3 333/4 17/8 9 87/8 103/4 83/4 111/4 27/8 67/8	278 734 11 20 30 31 2 914 9 11 9 1112 F 3 7	3 778 1138 2018 3014 3414 218 938 918 1114 914 1134 7 318	378 8 111/4 201/4 3012 3415 21/4 91/2 91/4 111/2 91/2 12 0 31/4	378 878 1138 2038 3034 3134 238 958 938 1134 934 1254 4 338	814 1112 2013 31 35 212 934 912 12 10 1212 H 315	83,8 1158 2058 311,4 351,4 23,4 97,8 958 121,4 101,4 123,4 \(\frac{\pi}{4}\)	312 812 1134 2034 3112 3512 278 10 934 1212 1012 13 1 334	33, 858 1178 2078 313, 353, 3 1018 978 123, 103, 133, 10 378	33, 83, 12 21 32 36 318 1014 10 13 11 1312 4 8	378 878 1218 2118 3214 3614 314 1038 1018 1314 1114 1334	4 9 12/4 2114 3212 3612 312 1013 1014 1312 1112 14 414	418 918 1258 2112 3234 3634 358 1058 1038 1334 1134 1414 438	37 378 103 1019 14 12 1419 419
Table of Inches for Draughting Shirts by Ir	From O down fol.  10 2 do.  20 3 do.  10 4 do.  10 5 do.  10 6 do.  10 8 do.  From O Cross lo  From 3 do.  From 3 do.  From 5 do.	1/2 23/4 7/2 103/4 197/8 293/4 333/4 17/8 9 87/8 103/4 63/4 111/4 27/8 67/8	34 278 734 11 20 30 31 2 914 9 11 9 1112 F 3 7	3/8 3 778 1138 2018 3014 3415 218 938 918 1134 914 1134 7 318	34 378 8 111/4 2014 3012 3415 21/4 912 91/4 1112 912 12 0 314	78 378 878 1138 2038 303 3131 238 958 958 1131 931 1214 F 338	1 3/4 8/4 111,2 201,2 31 35 21,2 934 91,2 12 10 121,2 H 31,5	138 33-16 838 1158 2058 3114 3514 234 978 958 1234 1034 1234 🖺 358	114 316 812 1134 2034 3112 3516 278 10 934 1212 1012 13 1 334	134 334 858 1178 2078 3134 3534 3 1018 978 1234 1034 1314 [] 378	114 334 834 12 21 32 36 318 1014 10 13 11 1312 4 8	158 378 878 1238 2118 3214 3614 314 1028 1018 1314 1114 1334	11/4 4 9 121/4 211/4 321/2 361/2 31/2 101/2 101/4 131/2 111/2 14 41/4	114 418 918 1258 2112 3234 3634 358 1058 1038 1334 1134 1414 438	11/4 41/4 91/4 123/4 213/4 33 37 37/8 10/3/4 10/5/14 12 141/5 41/5



THE

## TAILORS' GUIDE:

CONTAINING

SYSTEMS OF DRAUGHTING

## FROCK AND SACK COATS, PANTS,

VESTS AND SHIRTS,

WITH VALUABLE IMPROVEMENTS, WARRANTED SUPERIOR TO ANYTHING EVER OFFERED TO THE TRADE.

BY

L. E. COLE,

Practical Cutter for the past 30 years.

Copy R ght Secured Jan. 18, 1869.

## MILWAUKEE:

starr & son, book and job printers, 412 and 414 east water street.









